

FQI 2,5/10 BK

3460.4

Insulated cross-connector, No. of poles: 10, Mounting type: Plug in, Width: 50.9 mm, Colour: Black

Commercial

General

Colour: Black

Country of origin: CZ

Customs number: 85389099

GTIN (EAN): 4044211113490

Packaging unit: 10

Product description: Insulated cross-connector

Quantity unit: PC

Unit of weight: G

Weight per piece (including packaging): 6.9g

Weight per piece (not including packaging): 6.8g

Technical

Dimensions

Length: 4mm

Pitch size: 5.1mm

Width: 50.9mm

Ratings

Current load, max.: 24A

Max. voltage: 800V

Rated cross-section: 2.5mm²

Rated current: 24A

Connection data

No. of poles: 10

Further technical data

Insulation available: ✓

Mounting type: Plug in

Number of bridged terminals: 10

Touch protection is available: ✓

Materials

Flammability class UL 94: V-2

Insulation housing: Polyamide 6.6

Material: Copper

Surface: Tin-nickel

Working temperature, max.: 105°C

Working temperature, min.: -40°C

Approvals

Environment

Environmental Product Compliance

EU-POP Conform: Yes

PROP 65 Conform: Yes

REACH Candidate Substance Note: No

REACH Conform: Yes

REACH Reference date: 2026-02-04

RoHS Conform: Yes

TSCA Conform: Yes
