

Q 3

2423.0



Cross-connector, No. of poles: 3, Mounting type: Can be screwed on, Width: 14.2 mm, Rated cross-section: 2.5 mm², Colour: natural

Commercial

General

Colour: Natural

Country of origin: CZ

Customs number: 85389099

GTIN (EAN): 4044211052058

Packaging unit: 50

Product description: Cross-connector

Quantity unit: PC

Unit of weight: G

Weight per piece (including packaging): 2.46g

Weight per piece (not including packaging): 2.42g

Technical

Dimensions

Hole diameter: 2.8mm

Hole height: 2.5mm

Hole spacing (mid-point to mid-point): 5.1mm

Length: 4mm

Pitch size: 5mm

Slotted hole: ✓

Width: 14.2mm

Ratings

Contamination degree: 3

Rated cross-section: 2.5mm²

Rated current: 20A

Voltage with partition, max.: 400V

Voltage without partition, max.: 400V

Connection data

No. of poles: 3

Screw head: Slotted

Screw threading: M 2,5

Tightening torque, max.: 0.8Nm

Tightening torque, min.: 0.4Nm

Further technical data

Mounting type: Screwable

Number of bridged terminals: 3

Materials

Material: Copper

Surface: Tin-plated

Surface screw: Galvanized

Approvals

Environment

Environmental Product Compliance

EU-POP Conform: Yes

PROP 65 CAS 1 Percent maximum: 4%

PROP 65 CAS 1 Percent minimum: 0.1%

PROP 65 CAS 1 Substance: LEAD

PROP 65 Conform: No

REACH CAS 1 Number: 7439-92-1

REACH CAS 1 Percent maximum: 4%

REACH CAS 1 Percent minimal: 0.1%

REACH CAS 1 Substance: BLEI

REACH Candidate Substance Note: No

REACH Conform: No

REACH Reference date: 2025-06-25

RoHS Conform: Yes

RoHS Exception rule: 6c

SCIP: 140BB76D-8B55-40B7-98C9-D9E0662B7778

TSCA Conform: Yes

Accessories

Screwdriver



SDB 0,6x3,5

1086.0
